

BESCHREIBUNG

- RG 174/U is a coaxial cable with stranded copper clad steel wire and with a tinned copper wire braid shield.
- The material specification of the outer jacket is classified as Low Smoke Zero Halogen (LSZH) material.
- ECE R118.02 approved cable.



SPEZIFIKATIONEN

Elektrisch DE	
Geschwindigkeitsfaktor	0.66
Kapazität	100 - 3 pf/m
Impedanz	50 Ω
Mechanisch DE	
Beachtung	ECE R118.02 zugelassenes Kabel.
Innerer Leiter Dia / Matl	0.48 mm dia. (7 x 0.160 mm) Copper clad steel wire
Äußerleiter Dia.	ca. 1.8 mm
Dämm Material	1.5 mm dia. PE
Geflochtenes Material	Cu-verzinkt
Mindest. Biegeradius	21 mm
Gewicht	0.011 kg
Jacke Dia / Matl	dia. 0.15 mm LSZH
Geflochtene Abdeckung	85 %
Umwelt	
Betriebstemperaturbereich	-25 °C to +60 °C

ADDITIONAL DATA

ATTENUATION		
FREQUENCY	[dB/100m]	Max. HF-power/W
150 MHz	32.3	210
450 MHz	57.8	
900 MHz	83.6	
1400 MHz	106.1	
1800 MHz	122.1	
2200 MHz	137.0	
2500 MHz	147.2	
3000 MHz	165.7	